



ABOUND

[WWW.SOLIDATILE.COM](http://WWW.SOLIDATILE.COM)

804-256-3337

[SALES@SOLIDATILE.COM](mailto:SALES@SOLIDATILE.COM)

---

2280 DABNEY RD  
RICHMOND VA 23230

# ABOUND

Influenced by the classic beauty of marble, Abound is perfect for residential bathrooms and kitchens, thanks to its versatility in design. Abound can be used effortlessly throughout a room for a seamless design. A neutral color palette of both warm and cool tones complement virtually any setting, promising a lifetime of style and appeal.



## GLAZED CERAMIC FLOOR TILE



NIMBUS AB03



ASHEN AB04

### SIZES

|  |                    | THICKNESS | SQ. FT. /<br>CARTON | PIECES/<br>CARTON |
|--|--------------------|-----------|---------------------|-------------------|
|  | 12 x 24 Floor Tile | 3/8"      | 15.04               | 8                 |
|  | 12 x 12 Floor Tile | 5/16"     | 15.52               | 16                |

### TRIM

|  |                |       | NUMBER | PIECES/<br>CARTON |
|--|----------------|-------|--------|-------------------|
|  | Floor Bullnose | 3x12" | P-43C9 | 22                |

### INSTALLATION

#### RECOMMENDED GROUT JOINT:

3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)

### PERFORMANCE CHARACTERISTICS

|                     | ASTM# | RESULT     |
|---------------------|-------|------------|
| Water Absorption    | C373  | < 7.0%     |
| Breaking Strength   | C648  | > 250 lbs. |
| Scratch Hardness    | MOHS  | 8.0        |
| Chemical Resistance | C650  | Resistant  |
| Abrasion Resistance | C1027 | 4          |

### USAGE

| FLOORS | WALLS | COUNTERTOPS |
|--------|-------|-------------|
| F      | W     | C           |

### APPLICATIONS

|  | TARGET<br>DCOF WET | SUITABLE |
|--|--------------------|----------|
| Dry & Level - Interior Floor   | N/A                | ●        |
| Wet & Level - Interior Floor   | ≥ 0.42             |          |
| Shower Floors<br>(Residential or Light Commercial)   | ≥ 0.42             |          |
| Exterior Floor Applications<br>(including pool decking & other wet<br>areas with minimal footwear) | ≥ 0.60             |          |
| Ramps & Inclines   | ≥ 0.65             |          |
| Walls/Backsplashes   | N/A                | ●        |
| Countertops  | N/A                | ●        |
| Pool Linings   | N/A                |          |

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

### NOTES

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation.

## PRODUCTS

---

| STOCK NUMBER | COLOR  | SIZE             | APPLICATION  |
|--------------|--------|------------------|--------------|
| AOAB031212   | Nimbus | 12 x 12"         | Floor / Wall |
| AOAB031224   | Nimbus | 12 x 24"         | Floor / Wall |
| AOAB03P43C9  | Nimbus | 3 x 12" Bullnose | Trim         |
| AOAB041212   | Ashen  | 12 x 12"         | Floor / Wall |
| AOAB041224   | Ashen  | 12 x 24"         | Floor / Wall |
| AOAB04P43C9  | Ashen  | 3 x 12" Bullnose | Trim         |

[CLICK HERE TO LOG IN TO MTDECOR FOR PRICING AND AVAILABILITY](#)

TO PLACE AN ORDER OR SET UP AN ACCOUNT,  
CALL 804-256-3337 OR EMAIL SALES@SOLIDATILE.COM



ASHEN AB04



**solida tile**

2280 dabney rd  
richmond va 23230  
804•256•3337  
[www.solidatile.com](http://www.solidatile.com)